

2-CHANNEL TRANSMITTER with engraved stainless steel insert - black



RANGE 2-CHANNEL (PACKING BY 10)

09-0101 Black

TECHNICAL SPECIFICATIONS

POWER	SUPPLY

Supplied with 1 CR 2032 battery
--

DIMENSIONS (LXHXD)

41 x 71 x 13 mm

ENVIRONMENT
Operating temperature -20° C to +50° C
Storage temperature
-20° C to +70° C
Protection class IP54

- Affordable option for a variety of systems
- HF 868 MHz technology



GOOD TO KNOW

Equipped with an economizer of battery. A long press will no longer unload your transmitter.

SPECIFIC INFORMATION

Serial number	12 inlaid digits
868 Mhz	1
Number of channels	2
Technology	HF
Battery saver*	1
FEATURES	
Number of colours	1
Packaging	10
Programming in batches (barcode)	J
*Long push equivalent to 2 short pushes	

4-Channel transmitters

4-CHANNEL MIFARE BI-TECHNOLOGY TRANSMITTERS with engraved stainless steel insert

RANGE 4-CHANNELS (PACKING BY 10)

09-0115	Black	
09-0116	Blue	
09-0117	Red	
09-0118	Yellow	
09-0119	Green	

TECHNICAL SPECIFICATIONS

POWER SUPPLY

Supplied with **1 CR 2032 battery**

DIMENSIONS (LXHXD)

44 x 74 x 11 mm

ENVIRONMENT

Operating temperature -20° C to +50° C Storage temperature -20° C to +70° C Protection class IP54

• Can be used as both a key fob and a transmitter

• HF 868 MHz technology



The management website automatically detects the color

SPECIFIC INFORMATION		
Serial number	12 inlaid digits	
868 Mhz	1	
Number of channels	4	
Technology	MIFARE and HF	
Battery saver*	J	
Easy battery access	1	
FEATURES		
Number of colours	5	
Packaging	10	
*Long push equals 2 short pushes		