

SC-21-0200-0001-99

SmartCell Dual Smoke/Heat Detector

Overview

The SmartCell Dual Smoke / Heat Detector is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include dual smoke and/or heat detection, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Compact profile
- Flexible detection; smoke and/or heat
- Unique design
- Inbuilt locking mechanism

SC-21-0200-0001-99

SmartCell Dual Smoke/Heat Detector

Technical specifications

General

Wireless frequency	868 MHz
--------------------	---------

Electrical

Batteries	3 x ER14505M lithium thionyl chloride batteries (Fanso or Titus)
-----------	--

Detection

Sensitivity	Smoke: Normal, Normal+AVF. Heat: 58 °C, static (A2S), 58 °C rate of rise (A2R), 72 °C static (BS), 72 °C rate of rise (BR)
-------------	--

Physical

Physical dimensions	110 x 58 mm (Ø x D)
---------------------	---------------------

Net weight	0.2 kg
------------	--------

Colour	White
--------	-------

Mounting type	Ceiling mount
---------------	---------------

Environmental

Operating temperature	-10 to +55°C
-----------------------	--------------

Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
---------------------	---

Relative humidity	95% noncondensing max.
-------------------	------------------------

Environment	Indoor
-------------	--------

Regulatory

Compliance	CE
------------	----

Certification	CPR
---------------	-----

Standards	EN54-5 EN54-7 EN54-13 EN54-25
-----------	--



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 January 2024 - 11:39