

SC-31-0100-0001-99

SmartCell Red Sounder

Overview

The SmartCell Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-31-0100-0001-99

SmartCell Red Sounder

Technical specifications

General

Wireless frequency	868 MHz
--------------------	---------

Electrical

Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
-----------	--

Sounder

Output level	95 dB(A) at 1 m max.
--------------	----------------------

Output level adjustment	High or low
-------------------------	-------------

Selectable tones	32
------------------	----

Physical

Physical dimensions	110 x 72 mm (Ø x D)
---------------------	---------------------

Net weight	0.2 kg
------------	--------

Colour	Red
--------	-----

Mounting type	Wall mount
---------------	------------

Mounting position	Wall
-------------------	------

Environmental

Operating temperature	-10 to +55°C
-----------------------	--------------

Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
---------------------	---

Relative humidity	95% noncondensing max.
-------------------	------------------------

IP rating	IP21C
-----------	-------

Regulatory

Compliance	CE
------------	----

Certification	CPR
---------------	-----

Standards	EN54-3 EN54-13 EN54-25
-----------	------------------------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 30 January 2024 - 14:53