

Wireless Sounder *Product Datasheet*

Key Features

- Dual band 868MHz operation
- 32 selectable tones
- Integrated audio monitoring
- Sounder volume control
- Anti tamper locking mechanism
- Third party EN approved



Product Overview

The FireCell Wireless Sounder is quick and easy to install, offering individual addressing at the Fire Control Panel. This device comprises of a sounder and a wireless sounder base.

Features include dual band 868MHz operation, auto adjusting power output, 32 selectable tones, integrated audio monitoring, volume control and anti tamper locking mechanism.

This device is third party EN certified and compatible with the EMS FireCell system, EMS Fusion Radio Loop Module (RLM) and EMS Wireless Zone Monitor (WZM).

Technical Data

 -10°C to 55°C	 0 - 14 dBm (<i>auto adjusting</i>)	 CE10 0359-CPR-0022, 0359-CPR-0040
 3x AA / 3x C alkaline batteries	 120mm(Ø) 125mm(D)	 EN54-3 & EN54-25
 IP54, indoor use only	 0.65kg	 FC-171-002 (<i>Red Wireless Sounder Base Only</i>) FC-172-002 (<i>Red Sounder Only</i>)
 868MHz	 Up to 99dB(A) @ 1m	<i>Other variants available upon request.</i>