



Surface Magnetic Contact

Code: SC517/WH

SC517 | Surface Contact | Grade 1 | White | Non-resistored

This compact surface mounted magnetic contact can be used in security systems up to and including security grade 1 & environmental class II (for use indoors) as specified in EN50131-1 and is compliant to EN50131-2-6. It operates as a normally closed circuit going open when the magnet housing is moved away from the contact housing.

Features & Benefits

- 65 x 13.5 x 13mm
- 5 Terminals
- Operating Gap - 20mm
- EN50131-2-6 Grade 1
- Environmental Class II



Product Information

Connection type	Wired
-----------------	-------

Security

EN50131-2-6 Grade	1
-------------------	---

Environmental

EN50130-5 class	Class II
IP Rating	3X
Temperature range	-10°C - +40°C

Housing

Colour	White
Material	HIPS
Contact Dimensions (mm)	65 x 13 x 13
Magnet Dimensions (mm)	65 x 13 x 13

Electrical

Connection type	Wired
No. of terminals	5 Terminals
Contact type	Normally Closed
Contact Material	Palladium

Features

Mode of operation	SP
Operation Axes (X, Y, Z)	X, Y, Z
Pull-in gap (X, Y, Z)mm	5, 10, 20
Suitable for Double Door	No
No. of terminals	5 Terminals

