

## Overdoor Light c/w Sounder

Part No. **NC806CS**



### Overview

- Provides audible and visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series calling device.
- Indicates Standard calls via a constant tone/constant red light and Emergency calls via a pulsing tone/pulsing red light.
- Dual red LEDs and triangular diffuser make it highly visible from a distance.
- Mounts on a standard UK 25mm single gang flush or surface back box.
- Can also be used as an 'area indicator' at corridor junctions, staff workstations, etc.
- Finished in tough, durable ABS plastic.
- Also available as part of the NC951 Accessible Toilet Alarm kit.
- Stainless steel version also available.



### More Information

### Technical Specifications

|                           |   |
|---------------------------|---|
| Quiescent current         | 0mA (none).   |
| Alarm current             | Determined by the type of control equipment and number / type of field devices connected to the system.   |
| Indicators                | Dual ultra-bright red Alarm LEDs (lit constantly for standard calls, intermittently for emergency calls). |
| Controls                  | None (the device is controlled by the master calling device it is connected to).                          |
| Connections               | 1 (Signal); -Ve (Negative); +Ve (Positive).   |
| Onboard Sounder           | Yes. Sounds constantly for standard calls, intermittently for emergency calls.                            |
| Onboard Infrared Receiver | No.   |



Product dimensions (mm) 87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box.  
Construction & finish Plastic.  
IP Rating IP41.  
Weight 52g.  
Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom