

Overdoor light

Part No. **NC806C**



Overview

Provides visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series calling device.

Indicates Standard calls via a constant red light and Emergency calls via a pulsing red light.

Dual red LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Can also be used as an 'area indicator' at corridor junctions, staff workstations, etc.

Finished in tough, durable ABS plastic.

Also available as part of the NC951 Accessible Toilet Alarm kit.

Overdoor Lights c/w Sounders and Stainless steel version also available.

Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Dual ultra-bright red Alarm LEDs (lit constantly for standard calls, intermittently for emergency calls).
Controls	None (the device is controlled by the master calling device it is connected to).
Connections	1 (Signal); -Ve (Negative); +Ve (Positive).
Onboard Sounder	No.
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Translucent plastic.
IP Rating	IP41.
Weight	50g.



Operating conditions/temperature

-5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom