




1595

120-230VAC / 33VDC POWER SUPPLY UNIT



Power supply unit with input of 120÷230VAC, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).



1595

120-230VAC / 33VDC POWER SUPPLY UNIT

MAIN FEATURES

Supply voltage	120÷230 VAC
Output power supply voltage	33VDC
Max. current delivered (A)	0.5
Maximum inrush current (A)	1.2
Applicable to DIN rail	Yes
Number of DIN modules (n°)	4

GENERAL DATA

Height (mm)	62
Width (mm)	71.7
Depth (mm)	90
Type of finishing materials	Plastic
Product color	White
Operating temperature (°C)	-20 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes

ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	60
-----------------------------	----