

**6701W****SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET**

Wall-mounted colour monitor with 4.3" 16:9 screen and handset. Allows brightness and contrast control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with 4 soft touch buttons for door-opening, self activation, switchboard call, silent mode and with door status indicator LEDs. Manages floor door calls as standard. Option of adding 4 additional buttons with accessory art. 6733W. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Includes wall-mounting or residential series box backplate and riser distribution terminal art. 1214/2C. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 175x160x22mm.

AWARDSDESIGN
MILANO



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

GENERAL DATA

Height (mm)	160
Width (mm)	175
Depth (mm)	22
Product weight (g)	600
Product color	White RAL9003
Type of finishing materials	ABS
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

DISPLAY

Display size (")	4.3
Aspect Ratio	16:9
Resolution (pixels)	480x272

AUDIO FEATURES

Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (Ø) x 5.1 (H)mm, 100 ohm, 0.25W

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Absorption in stand-by (W)	0.13
Maximum absorption (W)	7.3



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Lock-release, Silent (Privacy), Door open
No. of programmable buttons for additional functions	2 (6 with accessory art. 6733W)
Clamps	L L CFP1 CFP2
Removable terminals	Yes

SETTINGS

Ringtone volume	Yes
Screen brightness control	Yes
Screen colour	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I (B1)
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES

Door opener	Yes
Automatic door opening on call (Doctor)	Yes
Silent mode (Privacy)	Yes
Self Activation	Yes
CPS call	Yes
Intercom calls	Yes
Outside door call input	Yes
Customisable ringtone	Yes
Sending alarm calls	Yes



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

GENERAL FEATURES

Actuator control	Yes
Multiple address	Yes
Door open signaling	Yes



6701W

SIMPLEBUS2 MINI DOOR ENTRY MONITOR WITH HANDSET

ACCESSORIES



6712A DESK BASE FOR MINI S2 MONITOR WITH HANDSET

Desk base installation accessory for Mini monitor with handset in Simplebus 2 system.



6711WS MINI HANDSET SMALL ADAPTER PLAQUE

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. White. Dimensions: 230x220x3mm.



6719W Access. cables external passage for MINI HS. S2

Wall support bracket for Mini monitor with handset allowing thru-routing of external cables.



6711W ADAPTER PLAQUE FOR MINI MONITOR W/ HANDSET. WHITE.

Mounting accessory for Mini Monitor when replacing Magis or Genius door entry monitors. Complete with backplate art. 6710. White. Dimensions: 300x270x3 mm.