



The Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.

#### **DECLARATION OF PERFORMANCE**

No. U0152

### 1. Unique identification code of the product-type:

# **Model number and Description:**

45681-702 Discovery Sounder Base (White)with Isolator

#### **Approved Accessories:**

45681-292 White Cap (Lockable) 45681-293 Red Cap (Lockable)

#### Product Type(s):

Sounders Short-circuit isolators

## 2. Intended use/es:

Fire detection and fire alarm systems installed in and around buildings Fire safety

#### 3. Manufacturer:

Apollo Fire Detectors Ltd, 36 Brookside Road, Havant, Hampshire, PO9 1JR, United Kingdom

#### 4. Authorised representative:

N/A

## 5. System of AVCP

System 1

### 6. Designated Standard(s)

EN 54-3:2001 + A1:2002 + A2:2006 EN 54-17:2005

#### **UK Approved Body:**

DBI Certification-UK Ltd (Approved Body 8504)

A HALMA COMPANY







Apollo Fire Detectors Limited

36 Brookside Road, Havant, Hampshire, PO9 1JR, UK t +44 (0)23 9249 2912 f +44 (0)23 9249 2754 e sales@apollo-fire.co.uk

www.apollo-fire.co.uk

# 7 Declared performance

Essential Characteristics	Standard EN54-3:2001 + A1:2002 + A2:2006	Performance
Performance under fire condition	4.2, 4.3, 5.2, 5.3	Pass
Operational reliability	4.4, 4.5, 4.6, 5.4, C4	Pass
Durability of operational reliability: temperature resistance	5.5, 5.6, 5.7, 5.8, 5.9	Pass
Durability of operational reliability: humidity resistance	5.8, 5.9, 5.10	Pass
Durability of operational reliability: corrosion resistance	5.11	Pass
Durability of operational reliability: shock and vibration resistance	5.12 to 5.15	Pass
Durability of operational reliability: electrical stability	5.16	Pass
Durability of operational reliability: resistance to ingress	5.17	Pass

<sup>5.6</sup> and 5.10 applies only to outdoor sounders or outdoor voice sounders.

<sup>5.16</sup> applies only to sounders or voice sounders with active electronic components.

Essential Characteristics	Standard EN54-17:2005	Performance
Performance under fire conditions	5.2 1)	Pass
Operational reliability	4	Pass
Durability of operational reliability: temperature resistance	5.4, 5.5	Pass
Durability of operational reliability: vibration resistance	5.9 to 5.12	Pass
Durability of operational reliability: humidity resistance	5.6, 5.7	Pass
Durability of operational reliability: corrosion resistance	5.8	Pass
Durability of operational reliability: electrical stability	5.3,5.13	Pass

<sup>1)</sup> This is assuming that the effect of the fire is to cause a short circuit in the transmission path that is protected by these devices



### 8 Online Display Location

This document can be viewed online at www.apollo-fire.co.uk

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with The Construction Products Regulation 2011 (retained EU law EUR 305/2011) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of Apollo Fire Detectors Limited by:

Mr. David Robbins Technical Director Havant – 25.10.2022

(v2)

